

Specification	Description	
PET	Type	PET
	Thickness	65 ± 10um
	Surface	Matt
	Colour Code	White
	Shrinkage	≤ 0.5mm
	Opacity	≥ 75%
	Whiteness	87 ± 3%
Adhesive	Type	Clear solvent based permanent, pressure sensitive glue
	Weight (g/m ²)	28 ± 5
	Adhesion Temperature	10°C ~ 40°C
	180° Peeling Force	≥ 14N/25mm 24H (FTM1)
	Initial Adhesion-Loop Tack	≥ 10N/25mm*25mm (FTM9)
	Holding Power	≥ 1440min (FTM8)
Liner	Type	Double sided polycoated kraft liner
	Colour	White
	Weight	120g ± 10g/m ²
	Release Force	0.05~0.10N/25MM
Storage Period	12 months under ordinary condition at temperature of 10°C-35°C and relative humidity of 50-60%	
Application	Indoor advertising	
Compatibility of Printers and Ink	Media is suitable for ECO digital printer, UV and LATEX. Inks should be the original ink from the printer manufacturers.	

Published information concerning bsmart products is based upon research which the company believes to be reliable although such information does not constitute a warranty. Due to the variety of uses of bsmart products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the products for each intended use and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.